# MARWELL CORPORATION

Manufacturer of UL Listed Meter Socket Adapters

WWW.MARWELLCORP.COM

PO BOX 139 MENTONE CA 92359

(909) 794-4192 FAX (909) 794-0250

### 2000 Series A-Base to Socket 2000 Series

12 Standard Models Detailed Below and on next page Inquire about specials.

DEAD FRONT OPTION AVAILABLE

TRONT OF HON AVAILABLE

### C/UL LISTED

Rated for Indoor or Outdoor Application. Threaded inserts for "Banjo Box" meter base. Grounding system standard on all models.

Tamper indicator on terminal cover, sealable retaining screw.


UL Listed, proprietary blend, fiberglass reinforced polycarbonate housing. All UL Listed Self-Contained units rated 125A Continuous - 150A Maximum


All UL Listed CT Rated units rated 30A Continuous 300V US - 240V Canada Rated
Optionally rated for 200A Max service at 160A Continuous.


**INDOOR AND OUTDOOR RATED** 

2000-3W-160-NR SHOWN

c UL) US
LISTED







<b>MODEL</b>	<b>SERVICE</b>	<b>METER</b>	<b>TERMINALS</b>	<u>JAWS</u>				
2000-2W-125A	2 WIRE	3 WIRE	4	4				
NOTE: #16 AWG WIRE, POTENTIAL LINK TO TERMINAL BLOCK.								
2000-2W-5J-125A	2 WIRE	3 WIRE	4	5				
NOTE: #12 AWG WIRE, 5TH JAW TO NEUTRAL JUMPER.								
2000-2W-2WM-125A	2 WIRE	2 WIRE	4	3				
NOTE: #12 AWG WIRE, UPPER RIGHT JAW TO NEUTRAL JUMPER.								
2000-3W-125A	3 WIRE	3 WIRE	4	4				
	2 WIRE	2 WIRE	4	4				







Consult Factory for Pricing and Availability.

## MARWELL CORPORATION

## Manufacturer of UL Listed Meter Socket Adapters


WWW.MARWELLCORP.COM


PO BOX 139 MENTONE CA 92359

(909) 794-4192 FAX (909) 794-0250

## 2000 Series A-Base to Socket









2000 Series Circuit Drawings









<b>MODEL</b>	<b>SERVICE</b>	<b>METER</b>	<b>TERMINALS</b>	<u>JAWS</u>			
2000-3W-5J-125A	3 WIRE	3 WIRE	4	5			
NOTE: #12 STRANDED WIRE, 5TH JAW THROUGH TERMINAL BLOCK.							
2000-3W-5J5T-125A	3 WIRE	3 WIRE	5	5			
NOTE: #12 SOLID COPPER WIRE, 5TH JAW TO 5TH TERMINAL IN TERMINAL BLOCK.							
2000-3W-6J CT Rated	3 WIRE	3 WIRE	4	6			
NOTE: #12 STRANDED WIRE, 5TH & 6TH JAW THROUGH TERMINAL BLOCK.							
2000-3W-6J6T CT Rated	3 WIRE	3 WIRE	6	6			
NOTE: #12 SOLID COPPER WIRE, 5TH & 6TH JAW TO TERMINALS IN TERMINAL BLOCK.							


#### **OPTIONS**

-160 RATED FOR 200A SERVICE AT 160 AMP CONTINUOUS CURRENT RATING.

- LG LESS GROUND, OMIT SURGE GROUND STRAPS.
- DS DEEP STOPS, EXTRA DEEP WIRE STOPS, 5/8 INCH DEEPER THAN NORMAL.







MODEL	<b>SERVICE</b>	<b>METER</b>	<b>TERMINALS</b>	<u>JAWS</u>			
2000-3S-2-3A CT Rated	2 WIRE	2 WIRE	4	5			
NOTE: 3S TO 3A TRANSFORMER RATED.							
2000-3S-2-3A-BP CT Rated	2 WIRE	2 WIRE	4	5			
NOTE: 3S TO 3A TRANSFORMER RATED WITH AUTOMATIC CURRENT BYPASS.							
2000-3W-2-6J-BP CT Rated	3 WIRE	3 WIRE	6	6			
NOTE: 3W TO 6J TRANSFORMER RATED WITH AUTOMATIC CURRENT BYPASS.							
2000-3W-2-6J6T-BP CT Rated	3 WIRE	3 WIRE	6	6			
NOTE: 3W TO 6J TRANSFORMER RATED WITH AUTOMATIC CURRENT BYPASS.							





