MARWELL CORPORATION Manufacturer of UL Listed Meter Socket Adapters

WWW.MARWELLCORP.COM

PO BOX 139 MENTONE CA 92359

(909) 794-4192 FAX (909) 794-0250

Specifications

Adapter rated for 200 Amp continuous when used in 200 Amp continuous socket.

Standard operating voltage is 240VAC. Grasslin Digi 20 or Digi 42 timer.

2 Week minimum battery carry over

-20 to + 140 Degrees F, Operating + or - 4 minutes per year 7 Day schedule

All timer leads terminated with quick FasTab connections for serviceability.

Power relay is mounted under the adapter floor and rated 35 Amp at 300V service.

4 jaws design with either 4, 5 or 6 stabs.

Fits ring or ringless sockets.

Patented, UL recognized, jaw design.

SPECIAL ADAPTERS Timer Adapters

Many utilities still have a water heater rate that is timer based and controlled by meters with built-in time clocks. These old time clock meters are difficult to repair or replace. The April 2001 copy of Marwell News offered one possible solution - relay adapters to be controlled by programmable meters. Another possible solution is a timer adapter.

The timer adapters can be programmed in your shop and delivered to the site ready for a plug and run installation. They can be fitted under any meter, including AMR equipped meters. Seven day scheduling is standard and automatic daylight savings time compensation is available. A simple solution for an old problem.

Options

- Available with 4, 5 or 6 stab configuration.
- Available with N/O (standard) or N/C relay contacts.
- 240V (standard) or 120V with neutral lead.
- Automatic daylight savings adjustment available.

Ordering Information 1000-R4-TIMER-???

We replace the ??? with your customer code and build them to your exact specification. Send us a sketch or contact Marwell for additional information.



